## **Fishing Vessel Safety Regulations**

This card is a summary. It is not meant to replace the Regulations. In case of disparities with the Regulations, the Regulations prevail.

| CARD # 3  |  |  |  |
|---|--|--|--|
| Hull Length:                                      | More than 12 m (39'-4")  |  |  |
| Voyages made :                                    | NC2 (maximum 25 miles from shore)  |  |  |
| Life Rafts and other<br>Life-saving<br>Appliances | Required One or more life rafts*, for 100% of the persons on board OR A combination of life rafts* AND recovery boats, for 100% of the persons on board * Coastal, reduced capacity or SOLAS life raft |  |  |
| EPIRB   | Required   |  |  |
| Immersion Suit or<br>Anti-exposure Work<br>Suit   | Required   |  |  |
| Lifejackets                                       | Required SOLAS OR Class 1 OR Class 2 OR Standard OR Small Vessel   |  |  |
| Reboarding Device                                 | Required   |  |  |
| Retrieval Apparatus                               | Required Except if only one person on board Except if recovery boat on board   |  |  |

| Hull Lengths                       | Personal Life-saving   | Visual Signals   | Firefighting  |
|------------------------------------|--|--|---|
| 3                                  | Appliances   | , and the second | Equipment   |
| > 12 m ≤ 15 m<br>> 39'-4" ≤ 49'-2" | -1 30 m (100') buoyant<br>heaving line<br>AND<br>-1 SOLAS lifebuoy with light<br>OR (100') 30 m buoyant<br>line                            | -1 watertight flashlight AND -12 pyro. distress signals (max. 6 smoke signals) AND -1 signalling mirror  | -1 2A:10B:C AND at each access where fuel-burning appliance -1 2A:10B:C AND -1 10B:C at engine room entrance AND -1 fire axe AND -1 bucket  |
| > 15 m<br>> 49'-2"                 | -1 30 m (100') buoyant<br>heaving line<br>AND<br>-1 SOLAS lifebuoy with 30<br>m (100') buoyant line<br>AND<br>-1 SOLAS lifebuoy with light | -1 watertight flashlight AND -12 pyro. distress signals (max. 6 smoke signals) AND -1 signaling mirror   | -1 2A:20B:C  AND at each access where fuel-burning appliance and at the entrance of each accommodation space -1 2A:20B:C  AND -1 20B:C at engine room entrance AND -1 fire axe AND -2 buckets |
| Fire Extinguisher Equivalents      | Dry Chemical ABC   | Dry Chem. BC   | CO <sub>2</sub>   |
| 1A :5B :C                          | 1.5 kg (3 lb)  |  |   |
| 2A :10B :C                         | 2.25 kg (5 lb)   |  |   |
| 2A :20B :C                         | 4.5 kg (10 lb)   |  |   |
| 5B :C                              | 1.5 kg (3 lb)  | 1.5 kg (3 lb)  | 2.25 kg (5 lb)  |
| 10B :C                             | 2.25 kg (5 lb)   | 2.25 kg (5 lb)   | 4.5 kg (10 lb)  |
| 20B :C                             | 4.5 kg (10 lb)   | 4.5 kg (10 lb)   | 9 kg (20 lb)  |